

The Union of Soviet  
Socialist  
Republics



USSR Council of Ministers  
State Committee for  
Inventions and Discoveries

# DESCRIPTION OF INVENTION

FOR CERTIFICATE OF  
AUTHORSHIP

(11) 578063

(61) Dependent Cert. of Auth.  
(22) Applied on /05/20/71 (21)  
**1662283/28-13**  
with inclusion of Application No.

(51) M. Cl.<sup>2</sup> A 61B 17/18

(32) Priority –  
(43) Published on 10/30/77.  
Bulletin No. 40  
(45) Date of publication of  
Description 11/22/77

(53) Universal Decimal  
Classification (YDK)  
**615.47:616.71-**

**-001.5-089.84:**  
**:616.728.2**  
**(088.8)**

A.I.Seppo

(72) Author of invention  
(71) Applicant

## (54) ENDO-ORTHOPEDIC DEVICE FOR HIP JOINT RECONSTRUCTION

1

The present invention refers to Orthopedics and Traumatology.

There is a known orthopedic endo-device for reconstruction of the hip joint, which contains threaded rods with a working cutting edge and shaped rods with a hollow conical head.

However, this device is intended for long term firm immobilization of fragments of a broken tubular bone.

The purpose of the present invention is to ensure a permanent gap between articular surfaces of a joint, which has been reduced after dislocation, deteriorated due to a pathological process or created by surgery, in rotation, flexion/extension and abduction/adduction for children.

To achieve this, the present endoprosthesis device is composed of two length-adjustable sleeves, which are connected by a spherical head and an arch-shaped guide-channel with edges of a different height. Free edges of the sleeves contain dentated conical apertures for shaped rod heads, which carry threaded rods.

Figure 1 shows the present orthopedic endoprosthesis device for reconstruction of the

2

hip joint, front view; figure 2 shows the same in a lateral view.

The device contains threaded rods 1 and 2 with working cutting parts 3 and 4, shaped rods 5 and 6 with hollow conical heads 7 and 8 and is composed of length-adjusted sleeves 9 and 10. The sleeves are connected by a movable joint composed of the spherical head 11 and arch-shaped guide-channel 12 with edges of different height 13. Free ends of the sleeves have dentated conical apertures 14 for shaped rod heads, which carry threaded rods 1 and 2.

Sleeve 9 is used to attach the device to the hip bone and ensures the necessary strength at the bone-metal interface, while sleeve 10 is used to attach the device to the tubular femur. By rotating the half-shaft 15 the surgeon can set the necessary gap between articular surfaces for the growth period.

### *Subject of Invention*

Endoprosthesis orthopedic device for reconstruction of the hip joint, containing threaded rods with hollow conical heads, which is distinguished by being composed of two length-adjusted sleeves, connected with a movable joint made of a conical hollow head

and an arch-shaped guide-channel with edges of different height, with dentated conical apertures in free ends of the sleeves for heads of shaped rods carrying the threaded rods, in order to achieve a permanent gap between articular

surfaces of joints reduced after dislocation, deteriorated due to a pathological process or created by surgery, in rotation, flexion/extension and abduction/adduction with children.

**578063**

